

- (35) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 3 1/2' dia. 8" high. T6N R24E
E 1/16 S27
LS 3848
1990
- (36) SET (FSM) 21" in ground. Cap stamped:
Raised rock mound 4' dia. by 9" high. T6N R24E
E 1/16 S27
C 1/4 - C
LS 3848
1990
- (37) SET standard Forest Service 3 1/4" Aluminum disc in
NW corner of granite slab, surface 2 1/2' x 4 1/2'. Disc stamped:
From which bear: T6N R24E
NE 1/16 S27
JP 5" DBH S.53"W., 7.35', scribed "NE 1/16 S27 BT", tagged LS 3848
1990
- (38) SET (FSM) 19" in side hill. Cap stamped:
Raised rock mound 5' dia. by 11" high. T6N R24E
N 1/16 S27
C 1/4 - C
LS 3848
1990
- (39) SET (FSM) 23" in ground. Cap stamped:
Raised rock mound 3' dia. by 7" high. From which bear: T6N R24E
W 1/16 S22
C 1/4 - C
LS 3848
1990
2" IP tagged RCE10467 per (R3) S.60°23'16"W., 21.93'
- (40) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4 1/5' dia. by 8" high. From which bears: T6N R24E
NW 1/16 S27
LS 3848
1990
1" IP tagged RCE10467 per (R3) S.61°12'56"W., 11.2'
- (41) SET (FSM) 21" in ground. Cap stamped:
Raised rock mound 4' dia. by 9" high. From which bears: T6N R24E
N 1/16 S28
C 1/4 - C
LS 3848
1990
1" IP tagged RCE10467 per (R3) S.60°12'56"W., 21.60'
- (42) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high. T6N R24E
S 1/16 S22
C 1/4 - C
LS 3848
1990
- (43) FOUND 5/8" Rebar tagged RCE30029 S.72°32'17"E., 0.36' from point for corner
(No reference for this monument). T6N R24E
SET (FSM) 9" into rocky hillside at point for corner. Cap Stamped: E 1/16
Deposit 5/8" Rebar along west side of monument. C 1/4 - C
Raised rock mound 6' dia. by 21" high. S22
LS 3848
1990
- (44) SET (FSM) 20" in ground. Cap stamped:
Raised rock mound 3' dia. by 10" high. T6N R24E
SE 1/16 S22
LS 3848
1990
- (45) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 3' dia. by 8" high. T6N R24E
S 1/16 S22
C 1/4 - C
LS 3848
1990
- (46) SET (FSM) 20" in ground. Cap stamped:
Raised rock mound 5' dia. by 10" high. T6N R24E
C 1/4 S22
LS 3848
1990
- (47) SET (FSM) 21" in ground. Cap stamped:
Raise rock mound 5' dia. by 9" high. T6N R24E
N 1/16 S22
C 1/4 - C
LS 3848
1990
- (48) FOUND 1" IP tagged RCE27104 per (R7) S.04°10'11"E., 0.35' from point for corner.
SET (FSM) 15" in ground at point for corner. Cap stamped:
Deposit 1" x 1.7' IP along south side of monument. T6N R24E
N 1/16 S21
C 1/4 - C
LS 3848
1990
Raise rock mound 5' dia. by 15" high.


- (49) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high. From which bear: T6N R24E
W 1/16 S10
C 1/4 - C
LS 3848
1990
2" IP tagged RCE10467 per (R5) N.24°34'00"W., 25.64'
- (50) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 3 1/2' dia. by 8" high. From which bear: T6N R24E
NW 1/16 S10
LS 3848
1990
2" IP tagged RCE10467 per (R5) N.25°02'14"W., 12.37'
- (51) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high. From which bear: T6N R24E
N 1/16 S9
C 1/4 - C
LS 3848
1990
2" IP tagged RCE10467 per (R5) N.34°06'43"W., 18.16'
- (52) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 42" dia. by 8" high. From which bear: T6N R24E
N 1/16 S28
C 1/4 - C
LS 3848
1991
2" IP tagged RCE10467 per (R3) S.76°57'28"W., 24.39'
- (53) SET (FSM) 23" in ground. Cap stamped:
Raised rock mound 3' dia. by 7" high. From which bears: T6N R24E
NW 1/16 S28
LS 3848
1991
1" IP tagged RCE10467 per (R3) S.77°20'13"W., 11.99'
- (54) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 42" dia. by 8" high. From which bear: T6N R24E
W 1/16 S28
C 1/4 - C
LS 3848
1991
1" IP tagged RCE10467 per (R3) S.83°05'51"W., 8.08'
- (55) SET (FSM) 20" in ground. Cap stamped:
Raised rock mound 3' dia. by 10" high. From which bears: T6N R24E
NE 1/16 S21
LS 3848
1990
1" IP tagged RCE27104 per (R7) N.88°13'19"W., 3.87'
- (56) FOUND 1" IP tagged RCE10467 per (R4) S.21°51'38"E., 0.24' from point for corner
SET (FSM) 20" in ground at point for corner. Cap stamped:
Deposit 1" x 24" IP along south side of monument. Raised T6N R24E
rock mound 3 1/2' dia. by 10" high. E 1/16 S21
LS 3848
1990
- (57) SET (FSM) 22" in ground. Cap stamped:
Raised rock mound 4' dia. by 8" high. From which bear: T6N R24E
C 1/4 S21
LS 3848
1991
1" IP tagged RCE27104 per (R7) N.89°20'42"W., 15.90'
- (58) SET (FSM) 22" in side hill. Cap stamped:
Raised rock mound 4' dia. by 8" high. From which bear: T6N R24E
W 1/16 S21
C 1/4 - C
LS 3848
1991
1" IP tagged RCE2704 per (R7) S.88°47'47"W., 7.94'
- (59) SET (FSM) 21" in ground. Cap stamped:
Raised rock mound 3' dia. by 9" high. From which bears: T6N R24E
SW 1/16 S21
LS 3848
1991
1" IP tagged RCE10467 per (R3) S.78°18'36"W., 11.98'
- (60) FOUND 1" IP tagged RCE10467 per (R3) S.66°39'49"E., 0.21' from point for corner,
SET (FSM) 22" in ground at point for corner. Cap stamped: T6N R24E
Deposit 1" x 24" IP along north side of monument. S 1/16
Raised rock mound 40" dia. by 8" high. S20
LS 3848
1991
- (61) FOUND 1" IP tagged RCE10467 per (R4) S.50°48'41"W., 0.55' from point for corner.
SET (FSM) 18" in rock at point for corner. Cap stamped: T6N R24E
Deposit 1" x 24" IP along south side of monument. E 1/16
Raised rock mound 5' dia. by 12" high. C 1/4 - C
S16
LS 3848
1990

- (62) SET standard Forest Service 3 1/4" aluminum disc on steep east facing basalt
extrusion. Disc stamped: T6N R24E
From which bear: C 1/4 S16
Tack in rock and tag (RCE 10467) per (R4) S.53"W., 0.18' LS 3848
1990
- (63) FOUND 1" IP in rock mound per (R4) S.71°35'54"W., 0.17' from point for corner.
SET (FSM) 21" in ground at point for corner. Cap stamped: T6N R24E
Deposit 1" x 24" IP along north side of monument. N 1/16 S16
Raised rock mound 3 1/2' dia. by 9" high. C
LS 3848
1990
- (64) FOUND 1" tagged RCE10467 per (R4) N.87°44'44"E., 0.19' from point for corner.
SET (FSM) 22" in ground at point for corner. Cap stamped: T6N R24E
Deposit 1" x 24" IP along north side of monument. NW 1/16 S16
Raised rock mound 4' dia. by 8" high. LS 3848
1990
- (65) FOUND 1" IP tagged RCE10467 per (R4) N.75°38'25"E., 0.36' from point for corner.
SET (FSM) 22" in ground at point for corner. Cap stamped: T6N R24E
Deposit 1" x 24" IP along north side of monument. W 1/16 S9
Raised rock mound 4' dia. by 8" high. LS 3848
1990
- (66) FOUND 2" IP stamped 1/4 COR 9-16 RCE10467 in imbedded 3' dia. rock mound per (R4).
Accepted as point for corner.
SET (FSM) 20" in ground in place of 2" IP. Cap stamped: T6N R24E
Deposit 2" IP along east side of monument. Rebuilt 1 S9
rock mound 3' dia. by 10" high. From which bear: LS 3848
1990
JP stump ±44" S.55"E., 118.9'. (R1) YP 36" S.55"E., 117.5'
NEW BT: J 8" DBH N.26"W., 39.5', scribed "1/4 S9 BT", tagged LS 3848

MONUMENT DESCRIPTION LEGEND

- (R1) 1878 GOVERNMENT SURVEY
(R2) 1925 GLO RESURVEY
(R3) 1 PM 66
(R4) 1 PM 80
(R5) 1 RS 31
(R7) 1 RS 98

- (GLOM) STANDARD 1" X 36" IP GENERAL LAND OFFICE SURVEY MONUMENT
WITH 2 1/2" BRASS CAP. (2" x 36" IP at Section corner)
(FSM) STANDARD 2" X 30" U.S. FOREST SERVICE ALUMINUM-MAGNETIC
SURVEY MONUMENT WITH 3 1/4" ALUMINUM CAP.
DBH DIAMETER BREAST HIGH (4 1/2' ABOVE HIGH SIDE GROUND LEVEL)
BT BEARING TREE LP LODGEPOLE PINE (TAMARACK)
RT REFERENCE TREE MM MOUNTAIN MAHOGANY
A ASPEN WBP WHITE BARK PINE
C COTTONWOOD WF WHITE FIR
J JUNIPER YP YELLOW PINE
JP JEFFREY PINE IP IRON PIPE



RECORD OF SURVEY No. 32-43
SECTIONS 9,10,16,20,21,22,27,& 28
TOWNSHIP 6 NORTH, RANGE 24 EAST, MDM.
COUNTY OF MONO STATE OF CALIFORNIA

JAMES NICKLOS (LS 3848) & ASSOCIATES

MAY 1992